

IN THE CLAIMS

Please cancel Claims 14-24.

1. (currently amended)      A system for generating hydrogen comprising:

feed water;

a liquid metal nuclear reactor having a non-radioactive secondary heat loop comprising a recirculated heat transfer medium;

a steam generator connected to said secondary heat loop, said heat transfer medium and said feed water passing through said steam generator, said steam generator capable of raising the temperature of said feed water;

a high temperature water cracking system, said feed water coupled to said water cracking system by a feed water input line, said secondary heat loop and said recirculated heat transfer medium being separate from said high temperature water cracking system; and

a topping heater, said topping heater capable of raising the temperature of said feed water so that said feed water in said high temperature water cracking system is at least about 850°C, said feed water input line coupled in flow communication with said steam generator, said topping heater, and said high temperature water cracking system, said feed water disassociated into hydrogen and oxygen in said high temperature water cracking system, said high temperature water cracking system being separate from all any secondary heat ~~loops~~ loop of said liquid metal nuclear reactor.

2. (original)      A system in accordance with Claim 1 wherein said feed water comprises output from at least one of a desalination plant, a water clean-up system, and a steam turbine condenser.

3. (original) A system in accordance with Claim 1 wherein said water feed input line is coupled to said steam generator, said steam generator raises the temperature of said feed water to between about 450°C to about 550°C.

4. (original) A system in accordance with Claim 3 wherein said feed water is coupled to said topping heater downstream from said steam generator, said topping heater raises the temperature of said feed water to at least 850°C

5. (original) A system in accordance with Claim 1 wherein said topping heater comprises a gas fired heater.

6. (previously presented) A system in accordance with Claim 5 further comprising a topping heater fuel, said topping heater fuel comprises a portion of said oxygen and hydrogen disassociated from said feed water in said high temperature water cracking system.

7. (previously presented) A system in accordance with Claim 5 further comprising a first regenerative heat exchanger and a topping heater exhaust line, said exhaust line coupled to said first regenerative heat exchanger to direct exhaust from said gas fired topping heater into said first regenerative heat exchanger, said feed water input line coupled to said first regenerative heat exchanger downstream of said steam generator.

8. (previously presented) A system in accordance with Claim 7 further comprising a first regenerative heat exchanger exhaust line, said first regenerative heat exchanger exhaust line coupled to a desalination plant to direct exhaust from said gas fired topping heater to said desalination plant after passing through said first regenerative heat exchanger.

9. (previously presented) A system in accordance with Claim 7 further comprising a second regenerative heat exchanger and a first regenerative heat exchanger exhaust line, said first regenerative heat exchanger exhaust line coupled to said second regenerative heat exchanger to direct exhaust from said gas fired topping heater to said second regenerative heat exchanger after passing through said first regenerative heat exchanger.

10. (previously presented) A system in accordance with Claim 9 further comprising a steam turbine and generator assembly, and a steam line, said steam line extending from said steam generator through said second regenerative heat exchanger to said steam turbine to direct a portion of an output of said steam generator through said second regenerative heat exchanger and to said steam turbine and generator assembly.

11. (previously presented) A system in accordance with Claim 1 further comprising a steam turbine and generator assembly, and a steam line, said steam line extending from said steam generator to said steam turbine to direct a portion of an output of said steam generator to said steam turbine and generator assembly to generate electricity.

12. (withdrawn) A system in accordance with Claim 11 wherein said topping heater comprises an electric heater, and a portion of said electricity generated by said steam turbine and generator assembly is used to power said electric topping heater.

13. (withdrawn) A system in accordance with Claim 1 further comprising an electricity producing fuel cell facility, and said topping heater comprises an electric heater, a portion of hydrogen and oxygen produced by said high temperature water cracking system is used as fuel in said electricity producing fuel cell, a portion of electricity produced by said fuel cell facility is used to power said electric topping heater, and water produced by said fuel cell facility is used as an addition to said feed water for said high temperature water cracking system.

14 - 24. (canceled)

25. (currently amended) A system for generating hydrogen comprising:

feed water;

a liquid metal nuclear reactor having a non-radioactive secondary heat loop comprising a recirculated heat transfer medium;

a steam generator connected to said secondary heat loop, said heat transfer medium and said feed water passing through said steam generator, said steam generator capable of raising the temperature of said feed water to between about 450°C to about 550°C;

a high temperature water cracking system, said feed water coupled to said water cracking system by a feed water input line, said secondary heat loop and said recirculated heat transfer medium being separate from said high temperature water cracking system; and

a topping heater, said topping heater capable of raising the temperature of said feed water so that said feed water in said high temperature water cracking system is at least about 850°C, said feed water input line coupled in flow communication with said steam generator, said topping heater, and said high temperature water cracking system, said feed water disassociated into hydrogen and oxygen in said high temperature water cracking system, said high temperature water cracking system being separate from all any secondary heat ~~loops~~ loop of said liquid metal nuclear reactor.

26. (original) A system in accordance with Claim 25 wherein said feed water comprises output from at least one of a desalination plant, a water clean-up system, and a steam turbine condenser.

27. (original) A system in accordance with Claim 25 wherein said topping heater comprises a gas fired heater.

28. (previously presented) A system in accordance with Claim 27 further comprising a topping heater fuel, said topping heater fuel comprises a portion of said oxygen and hydrogen disassociated from said feed water in said high temperature water cracking system.

29. (previously presented) A system in accordance with Claim 27 further comprising a first regenerative heat exchanger and a topping heater exhaust line, said exhaust line coupled to said first regenerative heat exchanger to direct exhaust from said gas fired topping heater into said first regenerative heat exchanger, said feed water input line coupled to said first regenerative heat exchanger downstream of said steam generator.

30. (previously presented) A system in accordance with Claim 29 further comprising a first regenerative heat exchanger exhaust line, said first regenerative heat exchanger exhaust line coupled to a desalination plant to direct exhaust from said gas fired topping heater said desalination plant after passing through said first regenerative heat exchanger.

31. (previously presented) A system in accordance with Claim 29 further comprising a second regenerative heat exchanger and a first regenerative heat exchanger exhaust line, said first regenerative heat exchanger exhaust line coupled to said second regenerative heat exchanger to direct exhaust from said gas fired topping heater to said second regenerative heat exchanger after passing through said first regenerative heat exchanger.

32. (previously presented) A system in accordance with Claim 31 further comprising a steam turbine and generator assembly, and a steam line, said steam line extending from said steam generator through said second regenerative heat exchanger to said steam turbine to direct a portion of an output of said steam generator through said second regenerative heat exchanger and to said steam turbine and generator assembly.

33. (previously presented) A system in accordance with Claim 25 further comprising a steam turbine and generator assembly, and a steam line, said steam line extending from said steam generator to said steam turbine to direct a portion of an output of said steam generator to said steam turbine and generator assembly to generate electricity.

34. (withdrawn) A system in accordance with Claim 33 wherein said topping heater comprises an electric heater, and a portion of said electricity generated by said steam turbine and generator assembly is used to power said electric topping heater.

35. (withdrawn) A system in accordance with Claim 25 further comprising an electricity producing fuel cell facility, and said topping heater comprises an electric heater, a portion of hydrogen and oxygen produced by said high temperature water cracking system is used as fuel in said electricity producing fuel cell, a portion of electricity produced by said fuel

cell facility is used to power said electric topping heater, and water produced by said fuel cell facility is used as an addition to said feed water for said high temperature water cracking system.